Support for collector shoe on carrier in pantograph of electric vehicle

Publication number:

DE4425460

Publication date:

1996-01-25

Inventor:

MUELLER HANS JOSEF (DE); WALBROEL BRUNO (DE)

Applicant:

RINGSDORFF WERKE GMBH (DE)

Classification:

- international:

B60L5/20; B60L5/18; (IPC1-7): B60L5/20; B60L5/28

- european:

B60L5/20B

Application number:

DE19944425460 19940719

Priority number(s):

DE19944425460 19940719

Also published as:


U See

FR2722737 (A1)

Report a data error here

Abstract of DE4425460

An electric vehicle has an overhead current collector with a contact shoe (3) on a carrier (2). The carrier has a groove (4), open to the base of the shoe and closed at the end faces. There is pressurised fluid in the groove. If a certain drop in the pressure occurs, the pantograph is lowered. The mouth (8) of the groove is covered with an elastic material which presses against the base of the shoe. The pressure channel is sealed from the contact shoe over its whole length with a seal (6). The closure seal is under pressure. The pressure drops if the seal is damaged due to pressure. The width of the mouth is between 0.5 and 5 millimetres. The groove is wider below the mouth than at the mouth; for example, it is a circular slot. The base of the shoe may be plane or have a channel in it.



Data supplied from the esp@cenet database - Worldwide

Monitoring device for a current collector sliding strip.

Publication number: EP0525595

Publication date:

1993-02-03

Inventor:

GRONDINGER GUENTER (AT); MUELLER GEORG DIPL-ING

(AT)

Applicant:

SIEMENS AG (DE)

Classification:

- international:

B60L5/20; B60L5/28; B60L5/18; (IPC1-7): B60L5/20

- european:

B60L5/20; B60L5/28

Application number: EP19920112464 19920721

Priority number(s): AT19910001496 19910726

Also published as:

EP0525595 (B1)

Cited documents:


DE8803377U EP0269307

DE3147453

Report a data error here

Abstract of EP0525595

A monitoring device for current collector sliding strips (1) is disclosed, in which a plurality of optical waveguides (4) are embedded in the current collector sliding strip. In this way, a continuous monitoring of the wear state of the current collector sliding strip is possible.



Data supplied from the esp@cenet database - Worldwide